



## Product Specification Guide

**Product:** 1.5 gpm "Jet-Stream Showerhead®, All Models

**Warranty:** **Twenty Years Limited Replacement Warranty, not subject to abuse or misuse. Product life expectancy is 30 years or more.**

**Rating:** Water & Energy Efficient Rated Upper 1% Of Class (all showerheads). Lowest Flow (1.5 gpm) & Highest User Acceptance (96%)

**Discounts:** Quantity Discounts Available

**Terms:** Payment Terms Are Net 10 Days, After Receipt Of Merchandise and we accept for payment Visa, MasterCard, Discover Card and PayPal. On approved credit, financing is available for large orders with monthly positive cash flow for up to 36 months, 25% Deposit Required. Purchase Directly Online [www.Jet-StreamShowerhead.net](http://www.Jet-StreamShowerhead.net)

**Shipment:** Normally within thirty days, large orders 120 days; the purchaser pays surface freight costs.

**Specifications:** **The new and improved, 1.5 gpm "Jet-Stream Showerhead® is precision engineered to cut shower-related utility (water, sewer & heated water) consumption 40% to 75% when compared to low flow or water saver (2.5-gpm) rated showers! It is the only 1.5 gpm (+/- 5%) constant-volume showerhead at all residential water pressures between 20-psi and 120-psi, is Self-Cleaning, Maintenance Free and carries a 20-Year Replacement Warranty.**

**Simple Test:** **In less than 1-Minute, the 40% minimum shower water saving is easily proven using a bucket of any size as follows:**

1. Before installing the 1.5 gpm "Jet-Stream" Showerhead®, turn on the current shower and adjust hot and cold-water valves all the way open for the maximum flow rate of the shower and feel the pressure of the current shower with your hand.
2. Place the bucket under the shower and capture all of the water for 30 seconds. If uncertain of the results, repeat the test and have a second person use the watch to time the test. Document the water output volume, pressure, feel, etc.
3. After installing the 1.5 gpm "Jet-Stream" Showerhead®, run the same test, for the same length of time and see and feel the pressure difference and determine the water & energy savings percentage. If the bucket is only half of the previous test, the savings is 50%. Document the water output volume, savings, pressure, feel, etc and the saving percentage on the form provided on the obverse and faxback toll-free to 1(877) NFL-DATA [635-3282].

**Note! If you have not replaced showers in the past two years with water-saver (2.5 gpm) showers, the estimated savings on shower water utility consumption is 50% or more.**

### Features & Benefits

- **Patented Technology (no restrictors), Performance & Satisfaction Guaranteed (96% user acceptance) All "new customer" purchases include a 30-Day Satisfaction Money-Back Guaranty.**
- **Self-Cleaning, Maintenance Free (reduced maintenance & replacement costs)**
- **20-Year Replacement Warranty and made of Chrome-Plated Brass, All Models (durable)**
- **Payback Normally Less Than 12 Months In Shower Related Utility Savings**

**K. H. "Skip" Haynes, Inventor & Patent Holder Since 1978**  
**E-mail: [Showerheadman@cox.net](mailto:Showerheadman@cox.net)**

## 2-Minute Installation Guide

Any Problems, Call Toll-Free (866) 520-0094

Page 2 of 2

Wednesday, February 18, 2015

The Rated In The Upper 1% Of Its Class 1.5 gpm "Jet-Stream" Showerhead<sup>®</sup> fits all standard ½-inch threaded shower arms (Adaptors are available to retrofit obsolete ball-type shower arms).

1. Remove the current showerhead from the shower arm extension, by hand or by using a crescent or pipe wrench.
2. Remove all grime or dirt from the shower arm extension with a damp rag or cloth. Wrap with plumbing tape if necessary to provide a smooth and clean connection. Note! Start the plumbing tape back 2-3 turns from the end.
3. Install Rated In The Upper 1% Of Its Class, The 1.5 gpm "Jet-Stream" Showerhead<sup>®</sup> and make sure the black seal/control valve is centered in the top of the connector before installing, turning the connector clockwise by hand until snug. Caution: do not over-tighten as this may damage the seal/control valve. Disassemble any model, for any reason, voids the 20-Year Warranty

Turn on the water and insure there a no leaks. Tighten as necessary by hand or with a wrench. Do not over-tighten as damage to the seal/valve may occur and the showerhead will not function as designed and often a loud ringing or knocking noise in the plumbing pipe line.

If you need assistance in making the calculations for gallons per minute, just Go To Internet: <http://www.Jet-StreamShowerhead.net/calc.html> and enter the information, bucket size and how long it takes to fill the bucket.

**Complete & Return Within 10 Days Via Toll-Free Fax to: 1(877) NFL-DATA [635-3282]**

Please Print or Type

Date: \_\_\_\_\_

Name/Title: \_\_\_\_\_ / \_\_\_\_\_  
E-Mail: \_\_\_\_\_  
Company: \_\_\_\_\_  
Address: \_\_\_\_\_  
City/St/Zip: \_\_\_\_\_  
Tel: \_\_\_\_\_ Fax: \_\_\_\_\_  
Cellular: \_\_\_\_\_  
Total # Showers: \_\_\_\_\_

### Current Shower Test Results Information:

Manufacturer's Name	Model No.	Gallons Bucket Size	Fill Time (Min/Sec)	Gallons Per/Min
---------------------	-----------	------------------------	------------------------	--------------------

How do you feel about the savings, pressure, effectiveness, qualify and performance of the current shower?  
 Excellent       Good       Fair       Poor

### 1.5 "Jet-Stream" Showerhead Test Results Information:

Manufacturer's Name	Model No.	Gallons Bucket Size	Fill Time (Min/Sec)	Gallons Per/Min
Jet-Stream Mfg, LLC	_____	_____	_____	_____

Comments (Pressure/Feel) \_\_\_\_\_

The estimated savings is: \_\_\_\_\_%

How do you personally feel about the savings, pressure, effectiveness, qualify and performance of the 1.5 gpm "Jet-Stream" Showerhead<sup>®</sup>?

Excellent       Good       Fair       Poor

**Complete & Return Within 10 Days Via Toll-Free Fax to: 1(877) NFL-DATA [635-3282]**

Web Site: [www.Jet-StreamShowerhead.net](http://www.Jet-StreamShowerhead.net)